




LIGHT WEIGHT / ECONOMIC E-PUMP

PU20M3N01B / PU20M4N01B / PU20DMP01B



Features:

- Light Weight and compact mechanism design
- Compares to Enerpac PUJ-1201B / PUJ-1401B
- 115VAC 50/60 HZ Universal Motor, starts under full load
- 10', 24 VAC pendant control for safety
- For use with generators or extension cords
- Designed for intermittent duty cycle.



* shown with optional external pressure adjustment knob



	Enerpac PUJ-1401B	BVA PU20M4N01B
Usable Oil	1 Gal.	1 Gal.
Reservoir Material	Plastic Reservoir	Steel Reservoir
Flow Rate @ Low Pressure	200 Cu. In. @ 200 PSI	133 Cu. In. @ 200 PSI (Measured)
Flow Rate @ High Pressure	20 Cu. In. @ 10,000 PSI	28 Cu. In. @ 10,000 PSI (Measured)
1st / 2nd Stage Pressure Setting	200 PSI / 10,000 PSI	1,200 PSI / 10,000 PSI
Control Valve	4 Way / 3 Pos.	4 Way / 3 Pos.
Motor Type	Universal	Universal
Horse Power	1.2 HP (0.9 KW) 0.5 HP (Catalog Shown)	0.94 HP (0.7KW) 1.0 HP
Current Draw	9.5 A (@10000 PSI)	10.0 A (@10,000 PSI)
Motor Voltage	115 VAC, 50/60 Hz	115 VAC, 50/60 Hz
Sound Level	85 - 89 dBA	80 - 85 dBA
Net Weight	44 Lbs (w/ plastic reservoir) 1 Gal. usable oil	37 Lbs (w/ metal reservoir) 1 Gal. usable oil

SFA Companies

10939 N. Pomona Ave. • Kansas City, MO 64153 • Tel: 816-891-6390 Fax: 816-448-2142
www.bvahydraulics.com • Email: sales@bvahydraulics.com